MATERIAL SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

Trade Name: (989)739-8050 **Emergency Telephone.** No:

Vulcan 65-PSS

Manufacturer: Vulcan Systems, LLC 5740 F-41, Oscoda, MI 48750

SECTION 2 – HAZARDOUS INGREDIENTS

This section covers the material from which this product is manufactured. The term "hazardous ingredients" should be interpreted as a term required and defined in OSHA hazard communication standard. This product contains toxic chemicals subject to the reporting requirements of section 313 of title III of SARA and CFR part 372.

INGREDIENT		OSHA PermissibleTime		
	%	CASE NO.	Exposure Limit (PEL)	Hazard
Sn	35-48	7440-31-5	2	R20/22
Ag	5/-10	7440-22-4	.01	R20/22
Sb	.0103	7440-36-0	.02	R20/22
ZINC CHLORIDE	15-40%	7646-85-7	1.0 mg/m^3	ACGIH
AMMONIUM CHLORIDE	3-7%	12125-02-9	10 mg/m^3	ACGIH
HYDROGEN CHLORIDE	7-13%	7647-01-0	7 mg/m^3	OSHA
METHYL ALCOHOL	1-5%	67-56-1	262 mg/m^3	ACGIH
BORIC ACID	0.1-1%	10043-35-3	10 mg/m^3	ACGIH
WATER	30-60%	7732-15-5		

SECTION 3 – PHYSICAL AND CHEMICAL CHARACTERISTICS

Gray, paste-like liquid with no characteristic odor.

SECTION 4 – FIRE AND CHEMICAL CHARACTERISTICS

Non-flammable. Welding arc and sparks can ignite combustible and flammable products. Refer to the Canadian standard "Safety in Welding and Cutting and Allied Procedures" for fire prevention and protection information during the use of welding and allied procedure. Extinguishing Media - Co2 or Dry Chemical Extinguisher.

SECTION 5 – HAZARDOUS DECOMPOSITION PRODUCTS

There are no stability considerations of conditions to avoid. There are no hazardous polymerization conditions to avoid.

No known incompatibility materials to avoid.

Hydrogen chloride, zinc oxide are listed as hazardous combustion or decomposition products.

SECTION 6 – HEALTH HAZARD

Causes severe burns to skin, eyes, and respiratory system. May be fatal if swallowed. Effects of chronic exposure- contact burns, dermatitis, possible liver and kidney effects. Effects of acute over

i acute overexposure.	
Swallowing:	Chemical burn to digestive system. Nausea, vomiting and possible shock.
Skin absorbtion:	Not classified as a skin absorbent.
Inhalation:	Irritant to respiratory system. Headache, cough, or fever. Preexisting lung disorders will be aggravated.
Skin contact:	Dermatitis, possible chemical burn. Preexisting skin disorders will be aggravated.
Eye contact:	Irritation to eyes, may burn eye surfaces, tearing. May result in blindness.

SECTION 7 - PRECATIONS FOR SAFE HANDLING AND USE

Read and understand manufacturer's instructions and the precautionary label on the product. See American National Standard z249.1 "Safety in Welding and Cutting" published by the American Welding Society. Maintain all exposure below the limits in section 5. Monitor the air to ensure that the levels are below the above mentioned limits. See AWS f1.1 "Methods for Sampling Airborne Particles Generated by Welding and Allied Procedures" and AWS f1.3 "Evaluating Constituents in the Welding Environment: A Sampling Strategy Guide."

Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases below TLVs (threshold limit values) in the workers' breathing zone and the general area. Train the welder to keep his head out of the fumes. Use respirable fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below the TLV.

Wear helmet or use a face shield with filter lens. Wear hand, head, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. Train the welder not to touch live electrical parts and insulate himself from work and ground.

Prevent waste from contaminating the surrounding environment, discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, and local regulations.

SECTION 8 – FIRST AID PROCEDURES

Swallowing:	Contains strong acid! Call a physician or poison control center.
Skin:	Wash skin thoroughly with soap and water to remove all residue. If rash develops, call a physician. Burns can be caused by prolonged contact.
Eyes:	Flush with water for at least 15 minutes to remove all residue. Get medical attention immediately. Blindness may result!

Vulcan Systems, LLC, believes this data to be accurate, but no warranty, expressed or implied, is made.