

**SECTION 1 – IDENTIFICATION**

**Trade Name:** Vulcan T-910-AH      **Manufacturer:** Vulcan Systems, LLC  
**Emergency Telephone. No:** (989)739-8050      5740 F-41, Oscoda, MI 48750

**SECTION 2 – HAZARDOUS IDENTIFICATION****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):**

Health, Skin corrosion/irritation, 1  
 Health, Specific target organ toxicity - Single exposure, 3  
 Health, Carcinogenicity, 1  
 Health, Specific target organ toxicity - Repeated exposure, 2

**GHS Hazard Statements:**

H314 - Causes severe skin burns and eye damage  
 H335 - May cause respiratory irritation  
 H350 - May cause cancer  
 H373 - May cause damage to organs through prolonged or repeated exposure  
 CGA-HG11 - SYMPTOMS MAY BE DELAYED.

**Hazards not otherwise classified (HNOC) or not covered by GHS:**

**Route of Entry:** Eyes; Skin

**Target Organs:** Throat; Nose, Respiratory system

**Inhalation:** Short term overexposure to welding fumes may result in discomfort such as: dizziness, nausea, or dryness or irritation of the nose, throat, lungs, and/or eyes.

**Acute Effects:** Irritating to the nose, throat and respiratory tract.

**Chronic Toxicity:** Chronic overexposure to welding fumes can result in: Chronic respiratory problems, iron build-up in the lungs, bone erosion, reduced pulmonary functions and nervous disorders.

**Eye Contact:** Fumes may be moderately irritating to the eyes. The bright light produced by the arc can damage the eyes.

**GHS Label elements, including precautionary statements:**

GHS Signal Word: **DANGER**

**GHS Hazard Pictograms:****GHS Precautionary Statements:**

P232 - Protect from moisture.  
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 CGA-PG27 - Read and follow the Safety Data Sheet (SOS) before use.

**SECTION 3 – COMPOSITION AND INFORMATION ON INGREDIENTS**

This information is protected by Trade-Secret

**SECTION 4 – FIRST AID PROCEDURES**

If overcome by smoke or fumes, remove the victim to fresh air and call for medical aid. Employ first aid techniques recommended by the Red Cross.

**SECTION 5 – FIRE-FIGHTING MEASURES**

Non-flammable. Welding arc and sparks can ignite combustible and flammable products. Refer to the Canadian standard "Safety in Welding and Cutting and Allied Procedures" for fire prevention and protection information during the use of welding and allied procedure. **Extinguishing Media** – Co2 or Dry Chemical Extinguisher.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

Not Applicable as product cannot leak or be spilled.

**SECTION 7 – HANDLING AND STORAGE**

Read and understand manufacturer's instructions and the precautionary label on the product. See American National Standard z249.1 "Safety in Welding and Cutting" published by the American Welding Society. Maintain all exposure below the limits in section 5. Monitor the air to ensure that the levels are below the above mentioned limits. See AWS f1.1 "Methods for Sampling Airborne Particles Generated by Welding and Allied Procedures" and AWS f1.3 "Evaluating Constituents in the Welding Environment: A Sampling Strategy Guide."

Prevent waste from contaminating the surrounding environment, discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, and local regulations.

**SECTION 8 – EXPOSURE CONTROL/PERSONAL PROTECTION**

This section covers the material from which this product is manufactured. The term "hazardous ingredients" should be interpreted as a term required and defined in OSHA hazard communication standard. This product contains toxic chemicals subject to the reporting requirements of section 313 of title III of SARA and CFR part 372.

**Ingredients:**

Cas#	%	Chemical Name
7782-42-5	0-0.35%	Carbon aka Graphite
7439-96-5	0.05-1.6%	Manganese compounds and fumes (as Mn)
7440-21-3	0.05-1.6%	Silicon
7440-47-3	0.05-13.5%	Chromium
7440-02-0	0.05-19%	Nickel, metallic and alloys
7439-98-7	0.005-5.5%	Molybdenum: soluble and insoluble compounds
7440-33-7	0.005-10%	Tungsten Metal Powder
1314-62-1	0.005-2.2%	Vanadium, pentoxide dust and fume
7439-89-6	46.1-99.785%	Iron
7440-32-6	0-0.15%	Titanium

**EXPOSURE LIMITS**

<u>CHEMICAL NAME</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Carbon aka Graphite	15 mg/m <sup>3</sup> TWA	10 mg/m <sup>3</sup>
Manganese compounds	5 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>
Silicon	10 mg/m <sup>3</sup> * = Total dust, <=Respirable fraction	10 mg/m <sup>3</sup> Total Dust
Chromium	1 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>
Nickel Metal	1 mg/m <sup>3</sup>	1.5 mg/m <sup>3</sup>
Soluble compounds, as Mo	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Tungsten	5 mg/m <sup>3</sup> TWA, 10mg/m <sup>3</sup> STEL	5 mg/m <sup>3</sup> TWA, 10 mg/m <sup>3</sup> STEL (inhalable)
Vanadium	0.05 mg/m <sup>3</sup> TWA	1 mg/m <sup>3</sup> TWA
Iron	10 mg/m <sup>3</sup> TWA (Total Dust)	10 mg/m <sup>3</sup> TWA (particles)
Titanium	10 mg/m <sup>3</sup> NL = Not Listed	10 mg/m <sup>3</sup>

Welding fumes cannot be classified simply. The composition and quantity of both are dependent on the metal being welded, the process, procedures, and alloys used. Other conditions which also influence the composition and quality of the fumes and gases to which workers may be exposed include coating on the metal being welded (such as paint, plating, or galvanizing), the number of welders, the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, and presence of contaminants in the atmosphere (ie, chlorinated hydrocarbon vapors from cleaning & degreasing activities).

Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases below TLVs (threshold limit values) in the workers' breathing zone and the general area. Train the welder to keep his head out of the fumes. Use respirable fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below the TLV.

Wear helmet or use a face shield with filter lens. Wear hand, head, and body protection, which help to prevent injury from radiation, sparks, and electrical shock. Train the welder not to touch live electrical parts and insulate himself from work and ground.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	N/A	Upper/lower flammability or exposure limits	N/A
Odor	N/A	Vapor Pressure	N/A
Odor threshold	N/A	Vapor density	N/A
pH	N/A	Relative Density	N/A
Melting point/freezing point	N/A	Solubility	N/A
Initial boiling point and boiling range	N/A	Flash point	N/A
Evaporation rate	N/A	Flammability	N/A
Partition coefficient	N/A	Auto-ignition temperature	N/A
Decomposition temperature	N/A	Viscosity	N/A

**SECTION 10 – STABILITY AND REACTIVITY**

Not Applicable

**SECTION 11 – TOXICOLOGICAL INFORMATION**

Not Applicable

**SECTION 12 – ECOLOGICAL INFORMATION**

Not Applicable

**SECTION 13 – DISPOSAL CONSIDERATIONS**

Not Applicable

**SECTION 14 – TRANSPORTATION INFORMATION**

Not Applicable

**SECTION 15 – REGULATORY INFORMATION**

Regulatory CODE Descriptions

RQ = Reportable Quantity  
 MASS = MA Massachusetts Hazardous Substances List  
 NJHS = NJ Right-to-Know Hazardous Substances  
 OSHAAC = OSHA Workplace Air Contaminants  
 PA = PA Right-To-Know List of Hazardous Substances  
 SARA313 = SARA 313 Title III Toxic Chemicals  
 TSCA = Toxic Substances Control Act  
 TXAIR = TX Air Contaminants with Health Effects Screening Level  
 CERCLA = Superfund clean up substance  
 EPCRAWPC = EPCRA Water Priority Chemicals  
 HWCRA = RCRA Hazardous Wastes  
 NRC = Nationally Recognized Carcinogens  
 PRIPOL = Clean Water Act Priority Pollutants  
 TOXICPOL = Clean Water Act Toxic Pollutants  
 ACUTERCRA = RCRA Acute Hazardous Wastes (P-List)  
 CSWHS = Clean Water Act Hazardous substances  
 EHS302 = Extremely Hazardous Substance  
 TXHWL = TX Hazardous Waste List

**SECTION 16 – OTHER INFORMATION**

Vulcan Systems, LLC, believes this data to be accurate, but no warranty, expressed or implied, is made.